

## V HEALTH HAZARDS B. SIGNS/SYMPTOMS OF OVEREXPOSURE

**INHALATION:** Irritation to throat & nose.  
**SKIN CONTACT:** Irritation or rash.  
**INGESTION:** See INGESTION below.  
**EYES:** Irritation due to high pH.

## V HEALTH HAZARDS C. FIRST AID EMERGENCY PROCEDURES

**INHALATION:** Remove to fresh air. Call a physician.  
**SKIN CONTACT:** Wash affected areas with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before reuse.  
**INGESTION:** Give two glasses of water and induce vomiting. Call physician IMMEDIATELY.  
**EYES:** Flush eyes with copious quantities of water. Consult a physician.

## VI REACTIVITY DATA

**MATERIAL IS STABLE:** Yes  
**CHEMICAL INCOMPATIBILITIES:** Acids  
**CONDITIONS TO AVOID:** None  
**HAZARDOUS DECOMPOSITION PRODUCTS:** None. HAZARDOUS POLYMERIZATION WILL NOT OCCUR

## VII SPILL OR LEAK PROCEDURES

**PROCEDURES FOR SPILL/LEAK:** Small spills should be absorbed with absorbent material. Large spills should have area diked to prevent spreading; pump liquid into a salvage tank and absorb remaining mater; shovel into container.

**NEUTRALIZING CHEMICALS:** None

**WASTE MANAGEMENT:** Comply with Federal, State and Local regulations.

## VIII SPECIAL PROTECTION INFORMATION

**GLASSES:** Safety goggles.  
**GLOVES:** Chemical resistant.  
**RESPIRATOR:** Use approved respirator if TLV is exceeded.  
**VENTILATION:** Adequate to keep airborne dusts level below PEL concentration.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** As required to minimize skin contact.

## IX SPECIAL PRECAUTIONS FOR HANDLING AND USE

**STORAGE SEGREGATION HAZARD CLASSES:**

\*\*\*\*ALWAYS SEGREGATE MATERIAL BY MAJOR HAZARD CLASS\*\*\*\*

**SPECIAL HANDLING/STORAGE:** Store under controlled temperatures – range 32° to 100°F Keep **from freezing**. Minimize skin contact. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles, including shoes, that cannot be decontaminate.

DO NOT transfer to unmarked containers. Keep container closed when not in use to reduce evaporation. DO NOT transfer to non-ferrous containers such as aluminum or galvanized drums which may react to produce FLAMMABLE gas. Never use pressure to empty container, as this may rupture container.

**SPECIAL WORKPLACE ENGINEERING CONTROLS:** See section VIII

**DY-KAST SUPPLY & EQUIPMENT CO.**  
1382 Lear Industrial Park  
AVON, OH 44011  
Ph: 440-937-7979 Fax: 440-937-7999  
Web Site: [www.dykast.com](http://www.dykast.com)

This information is (a) believed to be accurate as of the date of preparation, (b) provided to comply with applicable laws, (c) related solely to the routine use of the product in its original packaging, and (d) furnished without any warranty, express or implied (including without limitation implied warranties of merchantability and/or fitness for a particular purpose). Users of this product are solely responsible for all loss or damage arising directly or indirectly from its handling, storage, use and disposal.